# SAFETY DATA SHEET

# 1. Identification

Product number	1000023631
Product identifier	AERO-01PL 3000 COOL 7OZ,30%
Revision date	03-26-2015
Company information	Vectair Systems Inc. PO Box 11068 Memphis, TN 38134 United States
Company phone	1-877-697-7276
Version #	02
Supersedes date	12-05-2014
Recommended use	Air Freshener
<b>Recommended restrictions</b>	None known.

## 2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Causes serious	eye irritation. May cause drowsiness or dizziness.
Precautionary statement		
Prevention	flame or other ignition source. Pressurized cor	surfaces No smoking. Do not spray on an open ntainer: Do not pierce or burn, even after use. Avoid r handling. Use only outdoors or in a well-ventilated
Response	If inhaled: Remove person to fresh air and kee cautiously with water for several minutes. Rem Continue rinsing. Call a poison center/doctor if medical advice/attention. Collect spillage.	nove contact lenses, if present and easy to do.
Storage	Store in a well-ventilated place. Keep containe sunlight. Do not expose to temperatures exceed	
Disposal	Dispose of contents/container in accordance w	vith local/regional/national/international regulations.

Disposal Hazard(s) not otherwise classified (HNOC) Supplemental information

None.

None known.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	40 - 60
Diethylene Glycol Monoethyl Ether		111-90-0	10 - 20
Propane		74-98-6	10 - 20

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	2.5 - 10
Other components below reports	able levels		2.5 - 10

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

# 4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. and precautions for firefighters

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose equipment/instructions holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move **Specific methods** containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol. General fire hazards

#### 6. Accidental release measures

**Fire-fighting** 

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
Environmental precautions	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into
	drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 2 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

# Occupational exposure limits

Components		Туре		Va	alue	
Acetone (CAS 67-64-1)		PEL		24	00 mg/m3	
				10	000 ppm	
Propane (CAS 74-98-6)		PEL		18	300 mg/m3	
				10	000 ppm	
US. ACGIH Threshold Lin	mit Values					
Components		Туре		Va	alue	
Acetone (CAS 67-64-1)		STEL		75	50 ppm	
		TWA		50	00 ppm	
Isobutane (CAS 75-28-5)		STEL		10	000 ppm	
US. NIOSH: Pocket Guid	e to Chemical Haz	ards				
Components		Туре		Va	alue	
Acetone (CAS 67-64-1)		TWA		59	00 mg/m3	
				25	50 ppm	
Isobutane (CAS 75-28-5)		TWA		19	900 mg/m3	
				80	0 ppm	
Propane (CAS 74-98-6)		TWA		18	300 mg/m3	
					00.000	
				10	)00 ppm	
US. Workplace Environm	nental Exposure Le	evel (V	VEEL) Guides	10	iuu ppm	
US. Workplace Environm Components	nental Exposure Lo	evel (V Type	/EEL) Guides		alue	
Components Diethylene Glycol Monoethyl Ether (CAS	nental Exposure Lo	•	VEEL) Guides	Va		
Components Diethylene Glycol	nental Exposure Lo	Туре	VEEL) Guides	<b>V</b> :	alue 10 mg/m3	
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0)	nental Exposure Lo	Туре	VEEL) Guides	<b>V</b> :	alue	
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0) logical limit values		Туре	VEEL) Guides	<b>V</b> :	alue 10 mg/m3	
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0) logical limit values ACGIH Biological Expos	ure Indices	Туре		<b>V</b> a 14 25	alue 10 mg/m3 5 ppm	
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0) logical limit values ACGIH Biological Expos Components		Туре	VEEL) Guides Determinant	<b>V</b> :	alue 10 mg/m3	
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0) logical limit values ACGIH Biological Expos	ure Indices	Туре		<b>V</b> a 14 25	alue 10 mg/m3 5 ppm	
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0) logical limit values ACGIH Biological Expos Components	ure Indices Value 50 mg/l	Type TWA	Determinant Acetone	Va 14 25 Specimen	alue 10 mg/m3 5 ppm	
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0) logical limit values ACGIH Biological Expos Components Acetone (CAS 67-64-1) * - For sampling details, pl propriate engineering	ure Indices Value 50 mg/l ease see the source Good general should be mat or other engin	Type TWA TWA e docu ventila tched to teering ts have	Determinant Acetone ment. tion (typically 10 a o conditions. If ap controls to mainta	Va 14 25 <b>Specimen</b> Urine air changes per plicable, use pro ain airborne leve	alue 10 mg/m3 5 ppm	atio its.
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0) logical limit values ACGIH Biological Expos Components Acetone (CAS 67-64-1) * - For sampling details, pl propriate engineering trols	ure Indices Value 50 mg/l ease see the source Good general should be mat or other engin exposure limit eyewash stati	Type TWA TWA e docu ventila tched to heering ts have on.	Determinant Acetone ment. tion (typically 10 a o conditions. If ap controls to mainta not been establis	Va 14 25 <b>Specimen</b> Urine air changes per plicable, use pro ain airborne leve hed, maintain a	alue 0 mg/m3 5 ppm Sampling Time * hour) should be used. Ventilation rate bcess enclosures, local exhaust ventil ls below recommended exposure limi	atio its.
Components Diethylene Glycol Monoethyl Ether (CAS 111-90-0) Dogical limit values ACGIH Biological Expos Components Acetone (CAS 67-64-1)	ure Indices Value 50 mg/l ease see the source Good general should be mat or other engin exposure limit eyewash stati	Type TWA TWA e docu ventila tched to beering ts have on. nal pro	Determinant Acetone ment. tion (typically 10 a o conditions. If ap controls to mainta not been establis	Va 14 25 <b>Specimen</b> Urine air changes per plicable, use pro ain airborne leve hed, maintain a <b>nt</b>	alue 10 mg/m3 5 ppm Sampling Time * hour) should be used. Ventilation rate bcess enclosures, local exhaust ventil- ls below recommended exposure limi rborne levels to an acceptable level. I	atio its. I

Skin protection	
Other	Wear suitable protective clothing.
<b>Respiratory protection</b>	Chemical respirator with organic vapor cartridge and full facepiece.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

-	-
Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	132.89 °F (56.05 °C) estimated
Flash point	-5.0 °F (-20.6 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	1.6 % estimated
Flammability limit - upper (%)	14.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	270.47 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	0.314 estimated
10. Stability and reactivity	

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

#### Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### Information on toxicological effects

Acute toxicity	Narcotic effects.		
Components	Species	Test Results	
Acetone (CAS 67-64-1)			
Acute			
Dermal			
LD50	Guinea pig	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
	Rabbit	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
Inhalation			
LC50	Rat	55700 ppm, 3 Hours	
		132 mg/l, 3 Hours	
		50.1 mg/l	
Oral			
LD50	Rat	5800 mg/kg	
		2.2 ml/kg	
Diethylene Glycol Monoeth	yl Ether (CAS 111-90-0)		
Acute			
Dermal			
LD50	Guinea pig	5900 mg/kg, Days	
	Rabbit	8500 mg/kg, 2 Hours	
		8476 mg/kg, 24 Hours	
		7714 mg/kg	
Oral			
LD50	Guinea pig	4970 mg/kg	
	Mouse	6031 mg/kg	
	Rabbit	5600 mg/kg	
	Rat	5600 mg/kg	
		5.4 ml/kg	
Isobutane (CAS 75-28-5)		-	
Acute			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		-	

Components	Species		Test Results	
Propane (CAS 74-98-6)				
Acute				
Inhalation				
LC50	Mouse		1237 mg/l, 120 Minutes	
			52 %, 120 Minutes	
	Rat		1355 mg/l	
			658 mg/l/4h	
* Estimates for product may	be based on ad	lditional component data not shown.		
Skin corrosion/irritation	Prolonged s	kin contact may cause temporary irrita	tion.	
Serious eye damage/eye irritation	Causes seri	Causes serious eye irritation.		
Respiratory or skin sensitization	on			
Respiratory sensitization	Not availabl	e.		
Skin sensitization	This product is not expected to cause skin sensitization.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.			
OSHA Specifically Regulat Not listed.	ed Substances	s (29 CFR 1910.1001-1050)		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.			
Specific target organ toxicity - single exposure	May cause o	drowsiness and dizziness.		
Specific target organ toxicity - repeated exposure	Not classifie	d.		
Aspiration hazard	Not availabl	e.		
Chronic effects	Prolonged ir	nhalation may be harmful.		
12. Ecological informatio	n			
Ecotoxicity	Toxic to aqu	atic life with long lasting effects.		
Components		Species	Test Results	
Acetone (CAS 67-64-1)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	
Diethylene Glycol Monoethyl	Ether (CAS 11	1-90-0)		
Aquatic	-			

# Aquatic Fish LC50 Bluegill (Lepomis macrochirus) > 10000 mg/l, 96 hours \* Estimates for product may be based on additional component data pet above

\* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

## Bioaccumulative potential No data available.

Partition coefficient n	-octanol / water (log Kow)	
Acetone		-0.24
Diethylene Glycol Monoethyl Ether		-0.54
Isobutane		2.76
Propane		2.36
Mobility in soil	No data available.	

# Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

rei Biopocal concluciation	
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
US RCRA Hazardous Waste	U List: Reference
Acetone (CAS 67-64-1)	U002
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

# 14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	<ul> <li>Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.</li> </ul>
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### ΙΑΤΑ

UN1950
Aerosols, flammable
2.1
-
2.1
Not applicable.
Yes
10L
Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Allowed.
Allowed.
LTD QTY
UN1950
AEROSOLS
2.1
-
2.1

Packing groupNot applicable.Environmental hazardsYesMarine pollutantYesEmSF-D, S-USpecial precautions for userRead safety instructions, SDS and emergency procedures before handling. Read safety<br/>instructions, SDS and emergency procedures before handling. Read safetyPackaging ExceptionsLTD QTYTransport in bulk according to<br/>Annex II of MARPOL 73/78 andNot applicable.

the IBC Code DOT





Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated. CERCLA Hazardous Substance List (40 CFR 302.4) Acetone (CAS 67-64-1) Listed. SARA 304 Emergency release notification Not regulated. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed.

Superfund Amendments and Rea	uthorization Act of 1986 (SAI	RA)	
Hazard categories	Immediate Hazard - Yes		
C C	Delayed Hazard - No		
	Fire Hazard - Yes Pressure Hazard - No		
	Reactivity Hazard - No		
SARA 302 Extremely hazard	•		
Not listed.			
SARA 311/312 Hazardous	No		
chemical			
SARA 313 (TRI reporting) Not regulated.			
Other federal regulations			
-	112 Hazardous Air Pollutants	(HAPs) List	
Not regulated. Clean Air Act (CAA) Section	112(r) Accidental Release Pre	evention (40 CFR 68.130)	
Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)	()		
Safe Drinking Water Act (SDWA)	Not regulated.		
Drug Enforcement Admi Chemical Code Number	nistration (DEA). List 2, Essei	ntial Chemicals (21 CFR 1310.02(b) and <sup>2</sup>	1310.04(f)(2) and
Acetone (CAS 67-64-	•	6532	
-		cempt Chemical Mixtures (21 CFR 1310.1	l2(c))
Acetone (CAS 67-64- DEA Exempt Chemical N		35 %WV	
Acetone (CAS 67-64-	1)	6532	
US state regulations			
US. Massachusetts RTK - Su	bstance List		
Acetone (CAS 67-64-1)			
Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)			
,	Community Right-to-Know A	ct	
Acetone (CAS 67-64-1)			
Isobutane (CAS 75-28-5)			
Propane (CAS 74-98-6)	d Community Right-to-Know	L aw	
Acetone (CAS 67-64-1)		Law	
Isobutane (CAS 75-28-5)			
Propane (CAS 74-98-6)			
US. Rhode Island RTK			
Acetone (CAS 67-64-1) Isobutane (CAS 75-28-5)			
Propane (CAS 74-98-6)			
US. California Proposition 65	5		
	ater and Toxic Enforcement Action technologies and Toxic Enforcement Action technologies and the second second technologies and the second sec	t of 1986 (Proposition 65): This material is tive toxins.	not known to contain
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Chemic	cal Substances (AICS)	Yes
Canada	Domestic Substances List (DS	SL)	Yes
Canada	Non-Domestic Substances Lis	t (NDSL)	No
China		I Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Substances (EINECS)	g Commercial Chemical	Yes
Europe	European List of Notified Cher	nical Substances (ELINCS)	No

Inventory of Existing and New Chemical Substances (ENCS)

Japan

Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date Revision date Version #	12-05-2014 03-26-2015 02
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Product and Company Identification: Product Uses Physical & Chemical Properties: Multiple Properties Transport Information: Material Transportation Information GHS: Classification