

Extreme® Floor Stripper



High Power, Fast Acting, Low Odor, No-Rinse Floor Stripper

This high power high speed floor stripper was developed to penetrate and remove multiple coats of burnished floor finish with a minimum amount of labor. Utilizing the latest in technology, this powerful professional stripper unlocks the chemical bonds of acrylic and urethane fortified floor finishes releasing them from the floor surface and is suitable for use on most surfaces.

Features

Extremely Powerful.
Developed to quickly strip multiple coats of burnished finish from a variety of floors.
Rinse free - Has a lower pH than competitive formulas, requires no neutralization or rinsing.

Available In

4 - 1 Gal. Bottles Item #18404-00

55 Gal. Drum Item #18455-00

5 Gal Bag in Box Item #184B5-00

Directions for Use

Recommended for removing multiple coats of water-based acrylic and urethane fortified floor finishes from all types of resilient tile and hard surfaces. Not Recommended on linoleum or sheet vinyl floors. Pre-test in a small area; bleeding or discoloration may occur on linoleum, rubber tile, or asphalt tile. Sweep or dust mop floors or to remove any large debris. For light to medium strip, dilute 10 oz. /gal. (1:12). For heavy striping, dilute 25 oz. /gal. (1:5) with cold water. Apply solution liberally to floor surface. Allow 3-5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low speed rotary machine, automatic scrubber or stripping machine. Pick up solution with a wet vacuum, automatic scrubber or mop and bucket and thoroughly rinse the floor. Allow floors to dry completely before applying finish or sealer. No flood rinsing is necessary if surface appears free of dust and residue.

Tech Specs

| | |
|------------------------|---------------------|
| Color | Green |
| Flash Point | n/a |
| Fragrance | Lemon |
| Freeze/thaw stability | N/A |
| pH | 11.8 - 12.8 |
| pH @ dilution | 11.0 - 11.4 |
| Residue on evaporation | None |
| Warranty | 2 years |
| Specific gravity | 1.000 |
| Coverage | 400 sq. ft./ gallon |